

Codan 2820 Welding & Gas Hose



Codan 2820 - EN ISO 3821:2019

Flexible twin hose for acetylene and oxygen. Specially designed dividing groove allows easy separation for fitting to gas cylinder or welding gun. For use throughout industry for transporting acetylene and oxygen in mobile and stationary autogenic welding equipment. Normally installed using hose clamps and specially designed brass fittings. Please contact Codan for further information.

Please note that the 6.3 twin hose is manufactured with different ID dimensions:

- 6,3 = 6,3 / 6,3
- 6,8 = 6,3 / 8,0
- 6,9 = 6,3 / 9,0

Please contact Codan for further information.

Type nr. 2820

Application: Acetylene / Oxygen

Standard Length: 50 metres

Working Temperature: -40°C to 100°C

Inside: EPDM

Colour: Black

Reinforcement: Polyester

Outside: EPDM

Colour: Red/Blue

Standards: EN ISO 3821:2019

Std. branding: -

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
5,0	11,4	20	60	45	260	2820505000
6,3	13,5	20	60	60	340	2820606000
6,8	15,2	20	60	75	415	2820608000
6,9	16,4	20	60	80	480	2820609000
8,0	15,2	20	60	75	410	2820808000
9,5	16,7	20	60	90	450	2820959000